

INARCO® LF-31EPG

INARCO® LF-31EPG is a gel-like product for vertical or overhead application. The gel is suitable for the removal of paints, varnishes and resins. Due to its viscosity, it is possible to allow a long application time with a layer thickness of approx. 2mm, either selectively or over a wide area, without the product running. Due to the special composition, the product dries only after several hours, depending on the layer thickness, which allows long exposure times.

Fields of application:

Paints, varnishes, resins

Application:

- partially thixotropic, sprayable
- manual (brush, roller)

Properties:

- o no running, can be used selectively
- o very high efficiency, comparable, partly better than with solvents like acetone, thinner, etc.
- o no losses due to evaporation, no odor nuisance
- o non-flammable
- o no additional VOC emission
- o no hazardous material, high environmental and occupational safety
- o not suitable for solvent-sensitive materials (check material compatibility beforehand!)

Application concentration:

- o undiluted

Application temperature:

- o cold

pH-value:

- o pH-value (1% dilution) 5.5 – 6.5

Suitable for:

Materials not sensitive to corrosion and solvents like glass, ceramics, metals of all sorts

Disclaimer

All information about the product is based on the present state of knowledge. However, the information does not exempt the user from obtaining knowledge regarding material compatibility and effectiveness through his own tests. The demands on the product are very individual and can therefore not be generalized. Therefore, no warranty or liability claims can be made.

Status: 01.01.2022