

INARCO® LFZ-24CM

INARCO® LFZ-24CM is particularly suitable for removing marking paints and cured paints and varnishes. The dissolving speed of UV cured paints and varnishes is faster than INARCO LF-12CDB. The product does not leave a greasy film after drying and deposits the removed paints/varnishes on the floor. Only the sediment has to be disposed of, the rest can be used for permanent work. If the performance decreases, it can be increased again by "re-sharpening".

Fields of application:

Special inks and coatings, cured and with extreme film thickness

Application:

- immersion bath, also in circulation (for the desired sediment it needs 30-60 minutes standing time depending on the composition)
- Spraying and brushing plants (low-foaming)
- Ultrasonic systems
- manually

Properties:

- o low disposal costs (sediment, approx. ¼), no additional waste water, as permanently usable.
- o very high efficiency, comparable/better with solvents like acetone, thinner, etc.
- o no losses due to evaporation, no odor nuisance
- o non-flammable
- o no additional VOC emission
- o no hazardous material, high environmental and occupational safety
- o not suitable for solvent-sensitive materials (check material compatibility beforehand!)

Application concentration:

- o Removal of dried paints and varnishes: 20 - 50%.

Application temperature:

- o 20 – 80°C

pH-value:

- o pH-value (1%ige dilution) 6.5 – 7.5

Suitable for:

Materials not sensitive to corrosion and solvents like glas, ceramics, metals of all sorts

Disclaimer

All information about the product is based on the present state of knowledge. However, the information does not exempt the user from obtaining knowledge regarding material compatibility and effectiveness through his own tests. The demands on the product are very individual and can therefore not be generalized. Therefore, no warranty or liability claims can be made.

Status: 01.01.2022