

INARCO® ZV-22KL

INARCO® ZV-22KL is a VOC-containing (<20%) but non-flammable product for dissolving mainly cured and dried 2K paints and adhesives. The product does not leave a greasy film after drying and deposits the detached paints/lacquers on the floor. Only the sediment has to be disposed of, the rest can be used for permanent work. If the performance decreases, it can be increased again by "re-sharpening".

Fields of application:

Paints, varnishes and adhesives, especially in the dried or cured state, also 2K systems

Application:

- Immersion baths, also in circulation (for the desired sediment it needs 10-30 minutes standing time depending on the composition)
- Spraying and brushing plants (low-foaming)
- ultrasonic systems
- manually

Properties:

- o low disposal costs (sediment, approx. ¼), no additional waste water, as permanently usable.
- o very high efficiency, comparable with solvents such as acetone, thinner, etc.
- o no losses due to evaporation, no odor nuisance
- o non-flammable
- o no hazardous material, high environmental and occupational safety
- o not suitable for solvent-sensitive materials (check material compatibility beforehand!)

Application concentration:

- o 20 - 50%

Application temperature:

- o 20 – 80°C

pH-value:

- o pH-value (1%ige dilution) 6.5 – 7.5

Suitable for:

Materials not sensitive to corrosion and solvents like glas, ceramics, metals of all sorts

Disclaimer

All information about the product is based on the present state of knowledge. However, the information does not exempt the user from obtaining knowledge regarding material compatibility and effectiveness through his own tests. The demands on the product are very individual and can therefore not be generalized. Therefore, no warranty or liability claims can be made.

Status: 01.01.2022